

TECHNICAL DATA SHEET

PRODUCT: 2710005

DESCRIPTION: "TOP OIL" - FINISHING OIL BY SPRAYING

SUGGESTED USE: NAUTICAL FURNITURE, PARQUET FLOORING, DECKING AND FLAT PANELS

APPLICATION DEVICES SPRY GUN

STORAGE: KEEP CANS TIGHTLY SEALED, IN A WELL VENTILATED PLACE, WITH TEMPERATURE CONTROLLED BETWEEN 10 AND 30 °C

SHELF LIFE: 12 MONTHS FROM PRODUCTION DATE, IF STORED AS ABOVE

PHYSICAL CHARACTERISTICS

SPECIFIC GRAVITY @ 20°C	Kg/l	0.900 ± 1%
VISCOSITY @ 20 °C	sec.cup DIN 4	22 ± 10%
SOLIDS CONTENT	%	45 ± 1
SCHEEN	#	5 ± 1

READY TO USE BLEND

	PARTS BY WEIGHT	PARTS BY VOLUME
2710005	100	110
POT LIFE		UNLIMITED

SUBSTRATE

PARQUET FLOORING AND FLAT PANELS

APPLICATION

SUGGESTED COATING WEIGHT	80 to 100 g/sqm
SUGGESTED N° OF COATS	1 or 2 coats
TIME BETWEEN 2 COATS	6 hours

DRYING SCHEDULE AT ROOM TEMPERATURE

DUST FREE	2 hours
TOUCH DRY	4 hours
STACKABLE	10 hours, depending on weather conditions

GENERAL INFORMATION

THE PRODUCT IS CHARACTERIZED BY SUPERIOR WETTABILITY AND SOFT FEEL: ITS APPLICATION ON RAW WOOD PROVIDES A NATURAL LOOK.

THE PRODUCT CAN BE APPLIED ALSO BY BRUSH BOTH FOR PAINTING AND/OR MAINTENANCE OF SOLID WOODS OR VENEERS.

(#) SHEEN VALUE HAS BEEN DETERMINED BY APPLICATION OF A QUANTITY EQUAL TO 80 g/sqm BY SPRAY GUN.

IN CASE OF APPLICATION ON DECKING WE SUGGEST TO APPLY AT LEAST 4 COATS.

IN CASE OF NAUTICAL FURNITURE AND DECKING APPLICATION WE RECOMMEND A PERIODIC MAINTENANCE ACCORDING TO EXPOSURE AND WEATHER CONDITIONS.

NOTE: THE PRODUCT RESIDUALS ARE PRONE TO SELF IGNITION: DISPOSE OF ALL WASTE AND CONTAMINATED MATERIALS SAFELY AT THE END OF EACH WORKING DAY.

FOR HEALTH & SAFETY INFORMATION, PLEASE REFER TO RELEVANT MSDS.

Revision 8 dated 26 Aug 2013

2710005

This information is correct to the best of our knowledge. However, as the coating process depends on many variables and the actual application takes place without our supervision, we cannot assume any responsibility for the final result.