

**TIXAGENT SUPERCRYL****AkzoNobel**  
Tomorrow's Answers Today**GENERAL INFORMATION**

<b>Type of Product</b>	Additive
<b>Area of Use</b>	Interior Joinery
<b>Notes</b>	Additive used to increase the viscosity of SUPERCRYL Addition 0,5-1,0% (by weight) under thorough stirring. Addition 0,5% give same viscosity(din 6 mm) as SUPERCRYL TX. Addition 1,0% give the same thix as SUPERCRYL TX.

**BASIC MATERIAL PROPERTIES**

<b>Density</b>	Approx. 1,01 kg/l
<b>Shelf Life</b>	12 months in original, unopened package when stored following the storage conditions mentioned below. After the expiry date, contact our Technical Staff for an estimation of usability.
<b>Storage Conditions</b>	Between 15 and 25 °C under clean and dry conditions. Keep from freezing.

**HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION**

<b>HSE Information</b>	See Safety Data Sheet for further information.
------------------------	--

**DISCLAIMER**

For industrial use only.

The technical information and suggestions for use made herein are based on AkzoNobel's research and experience and are believed to be reliable, but such information and suggestions do not constitute a warranty. Since AkzoNobel has no control over the conditions under which the product is transported, stored, handled, used or applied, customer must himself determine the suitability of the product for the intended purposes. This technical data sheet replaces earlier versions. Unless expressly and specifically agreed in writing to the contrary, the customer will only enter into a contract with AkzoNobel under AkzoNobel's general sales conditions and AkzoNobel will not accept any subsequent terms and conditions of the customer.